星航★STAR

XHD400A | SMALL ELECTRIC LOADER



XHD400A : Exclusive advantages






Dashboard

Liquid crystal instrument panel

- Real-time and accurate display of voltage
- Have the functions of error operation prompt and fault code display



CHARGING PORT

4 to 6 hours of long battery life

- Easy charging



AXLE

Full suspension axle

- Riding comfort
- High carrying capacity



small electric loader

ELECTRICAL CONTROL COOLING

Mandatory forced air cooling for heat dissipation

• Grating protective cover, providing dual protection for internal components.

XHD400A/ XHDL400A



FLEXIBLE BODY






▲COMPACT BODY

The compact body design features a width of only 1060mm, making it highly suitable for operations in narrow spaces, such as narrow alleys, indoor buildings, feeding areas in livestock farms, and shopping malls - in these places, large machinery is difficult to achieve efficient operations, but this small electric loader can easily accomplish it.

▲QUICK - CHANGE CONNECTOR

The multi-functional tool switching function enables the equipment to be used in various ways, and is suitable for various operation scenarios.



WIDE RANGE OF OPERATIONS

▶Compact tail design

• Complete set of LED lighting warning lights, ensuring safety during both day and night operations.

• Flexible operation in a confined space.

• Ball-head type traction device, expanding the traction function.



▶Transmission system

• This framework adopts a lightweight hinged structure and shaft transmission design, featuring powerful power, a small steering angle and turning radius, excellent passage capacity, and flexible operability.



FEATURES AND FUNCTIONS




KEY FEATURES



▶The control lever is located on the right side of the seat, allowing the operator to maintain a better and more relaxed working posture and providing an excellent forward view.
▶Deep-pattern off-road engineering tires, excellent grip and anti-slip performance, thickened steel wheels, reliable load-bearing capacity, equipped with widened mudguards for protecting the vehicle body.





▶The joystick is on the same side as the control lever. By moving the joystick left and right, the pressure can be released, making the operation more convenient.
▶Hydraulic quick couplings feature a one-click quick replacement function, saving time and effort and significantly enhancing operational efficiency.



COMFORTABLE SEATA

The seat is equipped with seat belts and can be adjusted forward and backward.






LED LIGHT

Standard equipped with LED headlights, low-temperature resistant and shockproof.



FULL SUSPENSION VEHICLE AXLE

The axle is designed with full suspension reinforcement, which not only ensures riding comfort but also has excellent load-bearing capacity.



ATTACHMENTS



PERFORMANCE MATCHED

The multi-functional tool switching function enables the equipment to be used in various ways, meeting the needs of different operation scenarios. Specific tools such as fixtures and fork-shaped tools can be selected according to the specific work requirements.

Visit the website : www.xinghangmachinery.com



TRENCH FILLER

Optional sizes

- Size (mm): 1445 × 530 × 450
- Filling width (mm): 1100
- Weight (KG): 125



AUGER LEVERS

Optional Sizes

- Drilling diameter (mm): 150 - 600
- Drilling depth (mm): 1000
- Driving torque (N.m): 80

Customizable

- Diameter (mm): 150 × 1000
- Diameter (mm): 200 × 1000
- Diameter (mm): 250 × 1000
- Diameter (mm): 300 × 100



FORK

Optional sizes

- Size (mm): 1090×930×800
- Fork length (mm): 850
- Side shift size (mm): 2×150
- Rated load capacity (kg): 230
- Weight (kg): 105



LAWN MOWER

Optional sizes

- Size (mm): 1200×1230×480
- Mowing width (mm): 1100
- Mowing height (mm): 20 - 100
- Number of blades: 3
- Weight (kg): 185



4 IN 1 BUCKET

Optional sizes

- Size (mm): 1050 × 710 × 510
- Volume (m^3): 0.14 Opening (mm): 500
- Weight (kg): 115



SWEEPER

Optional sizes

- Size(mm): 1445 × 1100 × 580
- Brush diameter (mm): 500
- Cleaning width (mm): 1050
- Left-right swing angle (°): ±25
- Weight (kg): 145



HYDRAULIC BREAKER

Optional sizes

- Size (mm): 1165 × 615 × 265
- Drill Rod Diameter (mm): 45
- Pressure (Mpa): 8 - 12
- Impact Force (J): 80 - 100
- Weight (kg): 135



Excavator

Optional sizes

- Size (mm): 1100 × 670 × 700
- Slope angle (°): ±30
- System pressure (Mpa): 16
- Weight (KG): 90



TRENCHER

Optional sizes

- Size (mm): 1700 × 800 × 760
- Maximum trench depth (mm): 900
- Single trench width (mm): 150/200
- Trench link pitch (mm): 50.8
- Weight (kg): 178

ATTACHMENTS

GRABBING FORK

Optional Sizes

·Size (mm): 980*770*600

·Maximum Opening Angle (°): 88

·Rated Load Capacity (kg): 230

·System Pressure (Mpa): 16

·Weight (kg): 125



APPLICATION SCENARIO



PASTORALISM



CLEARING SNOW



AGRICULTURE





BACKYARD OF HOUSE

DETAILED PARAMETER CONFIGURATION

BASIC PARAMETERS

Name	Technical parameter	Name	Technical parameter
Model	XHD400A/XHDL400A	**Main materials used for the vehicle**	Manganese steel
Total weight of the machine	1240kg	**Loaded weight**	400kg
Lifting height	2600mm	**Discharge height**	1600mm
Chopper bucket size	1050*680mm	**Chopper bucket material**	Manganese steel
External dimensions (length * width * height)	3260*1050*2130(mm)	**Wheel base**	1450mm
Battery Type	Lead-Acid | Lithium Battery	**Battery Parameters**	60V/160Ah | 64V/150Ah or 64V/180Ah
Maximum battery life (continuous operating duration)	5–8 hours	**Charging interval**	8 hours
Hydraulic motor power	3KW*1	**Power of the drive motor**	2.5KW*2
Handle	Electronically controlled integrated system	**Turn**	Fluid-link steering
Tire Type	23*8.5-12	**Running speed**	High speed 0-14.5KM/h Low speed 0-8KM/h
Appearance	Integrated Liquid Crystal	**Driving Method**	All-Wheel Drive





COMPANY PROFILE

Jining Xinghang Machinery Manufacturing Co., Ltd. is located at No. 3, Ziwizi Road, Yanzhou District, Jining City, one of the six major machinery manufacturing centers in China. It is a pioneering enterprise in the electric compact equipment industry. Relying on two modern production bases and a complete industrial chain system, we focus on converting heavy power into flexible, efficient and environmentally friendly solutions.

Contact Us

WeChat1 WhatsAPP WeChat2

EMAIL： admin@xinghangmachinery.com

www.xinghangmachinery.com

星航★STAR